



TOWNSHIP OF HOPEWELL

MERCER COUNTY

201 Washington Crossing Pennington Road
Titusville, New Jersey 08560-1410
609.737.0605 Ext. 664
609.737.6839 Fax
September 8, 2016

Ms. Kimberly D. Bose, Secretary
Federal Energy Regulatory Commission
888 First Street, NE
Washington, DC 20426

**Re: Docket CP15-558-000
Proposed Gas Pipeline
PennEast Pipeline Company LLC
Hopewell Township, Mercer County**

Dear Ms. Bose:

Hopewell Township is classified as Tier A Municipality by the State of New Jersey for stormwater discharges. Hopewell Township operates under a Tier A Municipal Stormwater General Permit (NJPDES Permit No. NJ0141852) issued by the New Jersey Department of Environmental Protection (NJDEP).

The proposed PennEast pipeline is a Major Development as defined by the New Jersey Stormwater Management Rules, N.J.A.C. 7:8. Hopewell Township is obliged to review all major development for compliance with the New Jersey Stormwater Management rules (N.J.A.C. 7:8) under the terms of its Municipal General Permit, regardless if the NJDEP is reviewing those plans as well.

N.J.A.C 7:8-1.2 defines Major Development as "any "development" that provides for ultimately disturbing one or more acres of land or increasing impervious surface by one-quarter acre or more. Disturbance for the purpose of this rule is the placement of impervious surface or exposure and/or movement of soil or bedrock or clearing, cutting, or removing of vegetation." Projects undertaken by any government agency which otherwise meet the definition of "major development" but which do not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., are also considered "major development." N.J.A.C. 7:8-5.2(a) states "Stormwater management measures for major development shall be developed to meet the erosion control, groundwater recharge, stormwater runoff quantity, and stormwater runoff quality standards"

Certain aspects of the PennEast project are exempt. N.J.A.C. 7:8-5.2 exempts linear development projects from the groundwater recharge, stormwater runoff quantity, and stormwater runoff quality requirements at N.J.A.C. 7:8-5.4 and 5.5:

- a. The construction of an underground utility line provided that the disturbed areas are revegetated upon completion;
- b. The construction of an aboveground utility line provided that the existing conditions are maintained to the maximum extent practicable; and

Authority for Hopewell Township's jurisdiction under its NJPDES permit as a Tier A municipality for its MS4 discharges is through the Federal Clean Water Act:

- To protect water quality, and to satisfy the appropriate water quality requirements of the Clean Water Act, the MS4 State rules (N.J.A.C. 7:14A-25) require the NJDEP to issue permits regulating each small MS4. These MS4 permits specify the minimum control measures that must be implemented by the permittee in order to reduce the amount of pollutants discharged during storm events to the maximum extent practicable. Pursuant to 40 CFR 122.34(a), the implementation of best management practices, such as those prescribed in MS4 permits, is generally the most appropriate form of effluent limitations when designed to satisfy technology requirements and to protect water quality.
- The Federal Clean Water Act defines the term "effluent limit" broadly to include BMPs that would restrict the quantities, rates, and concentrations of constituent within a discharge. Thus, BMPs provide treatment pursuant to the Department's authority under the Clean Water Act with the goal of meeting water quality standards. Specifically, Section 402(p)(3)(B)(iii) of the Clean Water Act requires that permits for discharges from municipal storm sewers require:

"...controls to reduce the discharge of pollutants to the maximum extent practicable, including management practices, control techniques and system, design and engineering methods, and such other provisions as the Administrator or the State determines appropriate for the control of such pollutants."
- Similarly, inclusion of best management practices as effluent limitations is also consistent with the NJPDES Regulations at N.J.A.C. 7:14A-25.6(a)1 which states:

"Best management practice (BMP) requirements are generally the most appropriate form of effluent limitations when designed to satisfy technology-based requirements (including reductions of pollutants to the maximum extent practicable) and to protect water quality. Implementation of BMPs (other than OMs [Optional Measures]) consistent with the provision of the stormwater

Ms. Kimberly D. Bose, Secretary
September 8, 2016
Page 3 of 3

program required ...and the provisions of the NJPDES permit ... constitutes compliance with the standard of reducing pollutants to the maximum extent practicable.”

PennEast shall immediately make application to Hopewell Township for review of stormwater management measures for erosion control for the linear development where disturbed areas are revegetated upon completion. PennEast shall make application to Hopewell Township for the sections of the project where the utility is above ground and existing conditions are maintained to the maximum extent practicable.

The fact that there has been no submission to Hopewell Township for stormwater review is again demonstration that NEPA has not been complied with as environmental information related to stormwater management has not been made available to public officials and citizens before decisions are made. . . [and] [t]he information must be of high quality.” 40 C.F.R. 1500.1(b). Further the Council on Environmental Quality (CEQ) regulations on unavailable information are clear and if the information is obtainable and relevant to the project the agency must wait and obtain the information. 40 C.F.R. 1502.22.

Hopewell Township requests that PennEast immediately file make the appropriate application to Hopewell Township for reviews as described herein and further requests that FERC withdraw the DEIS and await the completion of all obtainable and relevant evaluations prior to republishing the DEIS.

Thank you.

Sincerely,



Kevin D. Kuchinski, Mayor

C: Hopewell Township Committee
Steven P. Goodell, Esquire
Governor Chris Christie
Senator Robert Menendez
Senator Cory Booker
Senator Shirley Turner
Congresswoman Bonnie Watson Coleman
Assemblywoman Elizabeth Maher Muoio
Assemblyman Reed Gusciora
Mercer County Board of Chosen Freeholders
Robert Martin, NJDEP Commissioner
John Gray, NJDEP Deputy Chief of Staff
Judith A. Enck, USEPA Region 2 Administrator

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

N.J.A.C. 7:8

STORMWATER MANAGEMENT

Statutory Authority: N.J.S.A. 12:5-3, 13:1D-1 et seq., 13:9A-1 et seq., 13:19-1 et seq., 40:55D-93 to 99, 58:4-1 et seq., 58:10A-1 et seq., 58:11A-1 et seq. and 58:16A-50 et seq.

Date last amended: June 20, 2016

For regulatory history and effective dates see the New Jersey Administrative Code

SUBCHAPTER 1: GENERAL PROVISIONS	4
7:8-1.1 Scope and purpose	4
7:8-1.2 Definitions	4
7:8-1.3 Program information	8
7:8-1.4 Severability	8
7:8-1.5 Relationship to other regulatory programs	8
7:8-1.6 Applicability to major development	9
SUBCHAPTER 2. GENERAL REQUIREMENTS FOR STORMWATER MANAGEMENT PLANNING	10
7:8-2.1 Scope	10
7:8-2.2 Goals of stormwater management planning	11
7:8-2.3 Stormwater management planning agencies	11
7:8-2.4 Stormwater management plan requirements	12
7:8-2.5 Exemptions	12
SUBCHAPTER 3. REGIONAL STORMWATER MANAGEMENT PLANNING	13
7:8-3.1 Scope	13
7:8-3.2 Regional stormwater management planning committee and lead planning agency	13
7:8-3.3 Regional stormwater management plan and elements	14
7:8-3.4 Characterization and assessment of the regional stormwater management planning area	15
7:8-3.5 Drainage area-specific water quality, groundwater recharge and water quantity objectives	18
7:8-3.6 Drainage area-specific design and performance standards	18
7:8-3.7 Selection of stormwater management measures	19
7:8-3.8 Strategy for implementing and evaluating effectiveness of stormwater management measures	20
7:8-3.9 Regional stormwater management plan review, adoption, and amendment and/or revision	20
7:8-3.10 Implementation of adopted regional stormwater management plan	21

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

SUBCHAPTER 4. MUNICIPAL STORMWATER MANAGEMENT PLANNING	21
7:8-4.1 Scope	21
7:8-4.2 Municipal stormwater management plan and elements	22
7:8-4.3 Schedule for adoption of municipal stormwater management plan and ordinances	23
7:8-4.4 County review process	24
7:8-4.5 Reservation of rights	25
7:8-4.6 Variance or exemption from the design and performance standards for stormwater management measures	25
SUBCHAPTER 5. DESIGN AND PERFORMANCE STANDARDS FOR STORMWATER MANAGEMENT MEASURES	25
7:8-5.1 Scope	25
7:8-5.2 Stormwater management measures for major development	26
7:8-5.3 Nonstructural stormwater management strategies	27
7:8-5.4 Erosion control, groundwater recharge and runoff quantity standards	28
7:8-5.5 Stormwater runoff quality standards	30
7:8-5.6 Calculation of stormwater runoff and groundwater recharge	33
7:8-5.7 Standards for structural stormwater management measures	34
7:8-5.8 Maintenance requirements	35
7:8-5.9 Sources for technical guidance	36
SUBCHAPTER 6. SAFETY STANDARDS FOR STORMWATER MANAGEMENT BASINS	37
7:8-6.1 Scope	37
7:8-6.2 Requirements for trash racks, overflow grates and escape provisions	38
7:8-6.3 Variance or exemption from safety standards	39
APPENDIX A	39

Subchapter 1: General Provisions

7:8-1.1 Scope and purpose

(a) This chapter establishes general requirements for stormwater management plans and stormwater control ordinances, as well as content requirements and procedures for the adoption and implementation of regional stormwater management plans and municipal stormwater management plans under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq.; the Water Quality Planning Act, N.J.S.A. 58:11A-1 et seq.; the Water Pollution Control Act, N.J.S.A. 58:10A-1 et seq.; and the Flood Hazard Area Control Act, N.J.S.A. 58:16A-50 et seq.; and implementing rules.

(b) This chapter establishes design and performance standards for stormwater management measures required by rules pursuant to the Flood Hazard Area Control Act, N.J.S.A. 58:16A-50 et seq.; the Coastal Area Facility Review Act, N.J.S.A. 13:19-1 et seq.; the Wetlands Act of 1970, N.J.S.A. 13:9A-1 et seq.; the Waterfront Development Law, N.J.S.A. 12:5-3; the Freshwater Wetlands Protection Act, N.J.S.A. 13:9B-1 et seq.; and the Dam Safety Act, N.J.S.A. 58:4-1 et seq.

(c) This chapter establishes safety standards for stormwater management basins pursuant to N.J.S.A. 40:55D-95.1.

7:8-1.2 Definitions

The following words and terms, when used in this chapter, shall have the following meanings unless the context clearly indicates otherwise.

"CAFRA Planning Map" means the geographic depiction of the boundaries for Coastal Planning Areas, CAFRA Centers, CAFRA Cores and CAFRA Nodes pursuant to N.J.A.C. 7:7E-5B.3.

"CAFRA Centers, Cores or Nodes" means those areas within boundaries accepted by the Department pursuant to N.J.A.C. 7:8E-5B.

"Compaction" means the increase in soil bulk density.

"Core" means a pedestrian-oriented area of commercial and civic uses serving the surrounding municipality, generally including housing and access to public transportation.

"County review agency" means an agency designated by the County Board of Chosen Freeholders to review municipal stormwater management plans and implementing ordinance(s). The county review agency may either be:

1. A county planning agency; or

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

2. A county water resources association created under N.J.S.A. 58:16A-55.5, if the ordinance or resolution delegates authority to approve, conditionally approve, or disapprove municipal stormwater management plans and implementing ordinances.

"Department" means the Department of Environmental Protection.

"Designated Center" means a State Development and Redevelopment Plan Center as designated by the State Planning Commission such as urban, regional, town, village, or hamlet.

"Design engineer" means a person professionally qualified and duly licensed in New Jersey to perform engineering services that may include, but not necessarily be limited to, development of project requirements, creation and development of project design and preparation of drawings and specifications.

"Development" means the division of a parcel of land into two or more parcels, the construction, reconstruction, conversion, structural alteration, relocation or enlargement of any building or structure, any mining excavation or landfill, and any use or change in the use of any building or other structure, or land or extension of use of land, for which permission is required under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq.

In the case of development on agricultural land, development means: any activity that requires a State permit; any activity reviewed by the County Agricultural Boards (CAB) and the State Agricultural Development Committee (SADC), and municipal review of any activity not exempted by the Right to Farm Act, N.J.S.A. 4:1C-1 et seq.

"Drainage area" means a geographic area within which stormwater runoff, sediments, or dissolved materials drain to a particular receiving waterbody or to a particular point along a receiving waterbody.

"Environmentally constrained area" means the following areas where the physical alteration of the land is in some way restricted, either through regulation, easement, deed restriction or ownership such as: wetlands, floodplains, threatened and endangered species sites or designated habitats, and parks and preserves. Habitats of endangered or threatened species are identified using the Department's Landscape Project as approved by the Department's Endangered and Nongame Species Program.

"Environmentally critical area" means an area or feature which is of significant environmental value, including, but not limited to: stream corridors; natural heritage priority sites; habitats of endangered or threatened species; large areas of contiguous open space or upland forest; steep slopes; and well head protection and groundwater recharge areas. Habitats of endangered or threatened species are identified using the Department's Landscape Project as approved by the Department's Endangered and Nongame Species Program.

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

"Empowerment Neighborhoods" means neighborhoods designated by the Urban Coordinating Council "in consultation and conjunction with" the New Jersey Redevelopment Authority pursuant to N.J.S.A. 55:19-69.

"Erosion" means the detachment and movement of soil or rock fragments by water, wind, ice or gravity.

"Impervious surface" means a surface that has been covered with a layer of material so that it is highly resistant to infiltration by water.

"Infiltration" is the process by which water seeps into the soil from precipitation.

"Lead planning agency" means one or more public entities having stormwater management planning authority designated by the regional stormwater management planning committee pursuant to N.J.A.C. 7:8-3.2, that serves as the primary representative of the committee.

"Major development" means any "development" that provides for ultimately disturbing one or more acres of land or increasing impervious surface by one-quarter acre or more. Disturbance for the purpose of this rule is the placement of impervious surface or exposure and/or movement of soil or bedrock or clearing, cutting, or removing of vegetation. Projects undertaken by any government agency which otherwise meet the definition of "major development" but which do not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., are also considered "major development."

"Municipality" means any city, borough, town, township, or village.

"Node" means an area designated by the State Planning Commission concentrating facilities and activities which are not organized in a compact form.

"Nutrient" means a chemical element or compound, such as nitrogen or phosphorus, which is essential to and promotes the development of organisms.

"Person" means any individual, corporation, company, partnership, firm, association, political subdivision of this State and any state, interstate or Federal agency.

"Pollutant" means any dredged spoil, solid waste, incinerator residue, filter backwash, sewage, garbage, refuse, oil, grease, sewage sludge, munitions, chemical wastes, biological materials, medical wastes, radioactive substance (except those regulated under the Atomic Energy Act of 1954, as amended (42 U.S.C. §§ 2011 et seq.)), thermal waste, wrecked or discarded equipment, rock, sand, cellar dirt, industrial, municipal, agricultural, and construction waste or runoff or other residue discharged directly or indirectly to the land, groundwaters or surface waters of the State, or to a domestic treatment works. "Pollutant" includes both hazardous and nonhazardous pollutants.

"Recharge" means the amount of water from precipitation that infiltrates into the ground and is not evapotranspired.

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

"Sediment" means solid material, mineral or organic, that is in suspension, is being transported, or has been moved from its site of origin by air, water or gravity as a product of erosion.

"Site" means the lot or lots upon which a major development is to occur or has occurred.

"Soil" means all unconsolidated mineral and organic material of any origin.

"State Development and Redevelopment Plan Metropolitan Planning Area (PA1)" means an area delineated on the State Plan Policy Map and adopted by the State Planning Commission that is intended to be the focus for much of the State's future redevelopment and revitalization efforts.

"State Plan Policy Map" is defined as the geographic application of the State Development and Redevelopment Plan's goals and Statewide policies, and the official map of these goals and policies.

"Stormwater" means water resulting from precipitation (including rain and snow) that runs off the land's surface, is transmitted to the subsurface, or is captured by separate storm sewers or other sewage or drainage facilities, or conveyed by snow removal equipment.

"Stormwater runoff" means water flow on the surface of the ground or in storm sewers, resulting from precipitation.

"Stormwater management basin" means an excavation or embankment and related areas designed to retain stormwater runoff. A stormwater management basin may either be normally dry (that is, a detention basin or infiltration basin), retain water in a permanent pool (a retention basin), or be planted mainly with wetland vegetation (most constructed stormwater wetlands).

"Stormwater management measure" means any structural or nonstructural strategy, practice, technology, process, program, or other method intended to control or reduce stormwater runoff and associated pollutants, or to induce or control the infiltration or groundwater recharge of stormwater or to eliminate illicit or illegal nonstormwater discharges into stormwater conveyances.

"Stormwater management planning agency" means a public body authorized by legislation to prepare stormwater management plans.

"Stormwater management planning area" means the geographic area for which a stormwater management planning agency is authorized to prepare stormwater management plans, or a specific portion of that area identified in a stormwater management plan prepared by that agency.

"Tidal Flood Hazard Area" means a flood hazard area, which may be influenced by stormwater runoff from inland areas, but which is primarily caused by the Atlantic Ocean.

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

"Urban Coordinating Council Empowerment Neighborhood" means a neighborhood given priority access to State resources through the New Jersey Redevelopment Authority.

"Urban Enterprise Zones" means a zone designated by the New Jersey Urban Enterprise Zone Authority pursuant to the New Jersey Urban Enterprise Zones Act, N.J.S.A. 52:27H-60 et seq.

"Urban Redevelopment Area" is defined as previously developed portions of areas:

1. Delineated on the State Plan Policy Map (SPPM) as the Metropolitan Planning Area (PA1), Designated Centers, Cores or Nodes;
2. Designated as CAFRA Centers, Cores or Nodes;
3. Designated as Urban Enterprise Zones; and
4. Designated as Urban Coordinating Council Empowerment Neighborhoods.

"Waters of the State" means the ocean and its estuaries, all springs, streams, wetlands, and bodies of surface or groundwater, whether natural or artificial, within the boundaries of the State of New Jersey or subject to its jurisdiction.

"Wetlands" or "wetland" means an area that is inundated or saturated by surface water or groundwater at a frequency and duration sufficient to support, and that under normal circumstances does support, a prevalence of vegetation typically adapted for life in saturated soil conditions, commonly known as hydrophytic vegetation.

7:8-1.3 Program information

Questions or submissions regarding this chapter should be directed to the Division of Watershed Management, New Jersey Department of Environmental Protection, PO Box 418, Trenton, New Jersey 08625.

7:8-1.4 Severability

If the provisions of any section, subsection, paragraph, or clause of this chapter shall be judged invalid by a court of competent jurisdiction, such order or judgment shall not affect or invalidate the remainder of any section, subsection, paragraph, or clause of this chapter.

7:8-1.5 Relationship to other regulatory programs

(a) Nothing in this chapter shall be construed as preventing the Department or other agencies or entities from imposing additional or more stringent stormwater management re-

quirements necessary to implement the purposes of any enabling legislation including those measures necessary to achieve the Surface Water Quality Standards at N.J.A.C. 7:9B.

(b) If a stormwater management measure is used as a soil erosion or sediment control measure, the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq., shall also apply.

(c) These stormwater requirements are the Department's standards referenced by the stormwater management provisions of the Residential Site Improvement Standards at N.J.A.C. 5:21-7.

7:8-1.6 Applicability to major development

(a) Except as provided in (b) below, all major development shall comply with the requirements of this chapter.

(b) The following major development shall be subject to the stormwater management requirements in effect on February 1, 2004, copies of which are available from the Department at the address specified in N.J.A.C. 7:8-1.3:

1. Major development which does not require any of the Department permits listed in (c) below and which has received one of the following approvals pursuant to the Municipal Land Use Law (N.J.S.A. 40:55D-1 et seq.) prior to February 2, 2004:

- i. Preliminary or final site plan approval;
- ii. Final municipal building or construction permit;
- iii. Minor subdivision approval where no subsequent site plan approval is required;
- iv. Final subdivision approval where no subsequent site plan approval is required; or
- v. Preliminary subdivision approval where no subsequent site plan approval is required;

2. Major development which has received one of the approvals pursuant to the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., in (b)1 above prior to February 2, 2004 and has secured at least one of the applicable permits listed in (c) below from the Department by February 2, 2004, and provided that the permit included a stormwater management review component; and

3. Major development undertaken by any government agency, which does not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., provided that the project has secured at least one of the applicable Department permits listed in (c) below prior to February 2, 2004, and provided that the permit included a stormwater management review component.

(c) For the purposes of this section, the term "permit" shall include transition area waivers under the Freshwater Wetlands Protection Act. In order to qualify under (b)2 or 3 above, the major development must have obtained at least one Department permit granted under

the following statutes and, provided that the permit included a stormwater management review component, prior to February 2, 2004:

1. Flood Hazard Area Control Act, N.J.S.A. 58:16A-50 et seq.;
2. Freshwater Wetlands Protection Act, N.J.S.A. 13:9B-1 et seq.;
3. Coastal Area Facility Review Act, N.J.S.A. 13:19-1 et seq.; or
4. Waterfront and Harbor Facilities Act, N.J.S.A. 12:5-3;

(d) An exemption provided by (b) above shall expire with the expiration, termination or other loss of duration or effect of either of the qualifying local approval or Department permit, whichever comes first. The expiration of local approvals under (b)1 above shall be governed by local ordinance. In the event there are multiple qualifying Department permits under (c) above, the expiration date is governed by that permit which expires last provided that the permit is still in effect. Once the exemption expires, the major development shall be subject to all requirements of this chapter upon reapplication for that permit and all subsequent permits or local approval(s) under the Municipal Land Use Law.

(e) An exemption under (b) above is limited to the land area and the scope of the project addressed by the qualifying approval(s) and permit(s). Exemptions under this section shall be deemed void if revisions are made to the qualifying approval or permit in (b) above, including approvals under the Municipal Land Use Law, unless upon application, the Department determines that each revision would have a de minimis impact on water resources. In making this determination, the Department shall consider the extent of any impacts on water resources resulting from the revision, including, but not limited to:

1. Increases in stormwater generated;
2. Increases in impervious surface;
3. Increases in stormwater pollutant loading;
4. Changes in land use;
5. New encroachments in special water resource protection areas; and
6. Changes in vegetative cover.

(f) In case of conflict with the Coastal Permit Program rules at N.J.A.C. 7:7-4.4(a)4, the requirements of this chapter shall supersede.

SUBCHAPTER 2. GENERAL REQUIREMENTS FOR STORMWATER MANAGEMENT PLANNING

7:8-2.1 Scope

This subchapter provides general principles applicable to all stormwater management plans and stormwater control ordinances, including the goals of stormwater management

planning, the process for identification of stormwater management planning agencies, and stormwater management plan requirements.

7:8-2.2 Goals of stormwater management planning

(a) All stormwater management plans and stormwater control ordinances shall be designed to:

1. Reduce flood damage, including damage to life and property;
2. Minimize, to the extent practical, any increase in stormwater runoff from any new development;
3. Reduce soil erosion from any development or construction project;
4. Assure the adequacy of existing and proposed culverts and bridges, and other in-stream structures;
5. Maintain groundwater recharge;
6. Prevent, to the greatest extent feasible, an increase in nonpoint pollution;
7. Maintain the integrity of stream channels for their biological functions, as well as for drainage;
8. Minimize pollutants in stormwater runoff from new and existing development in order to restore, enhance and maintain the chemical, physical, and biological integrity of the waters of the State, to protect public health, to safeguard fish and aquatic life and scenic and ecological values, and to enhance the domestic, municipal, recreational, industrial and other uses of water; and
9. Protect public safety through the proper design and operation of stormwater management basins.

7:8-2.3 Stormwater management planning agencies

(a) The following entities may be stormwater management planning agencies provided they are authorized under their enabling legislation to prepare stormwater management plans:

1. A municipality;
2. A county;
3. A county water resources agency or association;
4. A designated planning agency under N.J.A.C. 7:15;
5. A Soil Conservation District, in coordination with the State Soil Conservation Committee;
6. The Delaware River Basin Commission;

7. The Pinelands Commission;
8. The Delaware and Raritan Canal Commission;
9. The New Jersey Meadowlands Commission;
10. The Department; or
11. Other regional, State or interstate agencies.

7:8-2.4 Stormwater management plan requirements

- (a) A stormwater management plan shall include structural and nonstructural stormwater management strategies necessary to meet the stormwater management goals of this chapter.
- (b) A regional stormwater management plan shall comply with the requirements of this subchapter and N.J.A.C. 7:8-3.
- (c) A municipal stormwater management plan shall comply with the requirements of this subchapter and N.J.A.C. 7:8-4.
- (d) A stormwater management plan shall incorporate the safety standards for stormwater management basins at N.J.A.C. 7:8-6.
- (e) In developing a stormwater management plan and identifying appropriate stormwater management measures thereunder, each stormwater management planning agency shall consider the physical characteristics and ecological resources of the stormwater management planning area.
- (f) A stormwater management plan and any stormwater management ordinance shall be coordinated with any other stormwater management plans related to the same river basin or drainage area.

7:8-2.5 Exemptions

A municipality or other entity conducting stormwater management planning under this chapter may petition the Department at the address provided at N.J.A.C. 7:8-1.3 for an exemption to the requirements of this chapter by submitting documentation to demonstrate that, if granted, the exemption will not result in an increase in flood damage, water pollution, including threats to the biological integrity, or constitute a threat to the public safety.

SUBCHAPTER 3. REGIONAL STORMWATER MANAGEMENT PLANNING

7:8-3.1 Scope

(a) This subchapter describes stormwater management planning and implementation at the regional level, including plan elements; planning process; characterization; development of drainage area-specific objectives and standards; selection of stormwater management measures; strategy for implementing the measures and evaluating the effectiveness of the regional stormwater management plan; plan review, adoption, amendment or revision; and implementation and periodic evaluation of the plan.

(b) A regional stormwater management plan shall address stormwater-related water quality, groundwater recharge and/or water quantity impacts of new and existing land uses in a regional stormwater management planning area. A regional stormwater management planning area shall consist of one or more continuous drainage areas. For example, a drainage area could be an area defined by a hydrologic unit code 14 (HUC14) as defined by the United States Geological Survey.

7:8-3.2 Regional stormwater management planning committee and lead planning agency

(a) A regional stormwater management planning committee (the committee) shall be established for the purposes of creating a regional stormwater management plan.

(b) A person or entity seeking to establish a regional stormwater management committee shall solicit participation from municipalities, interstate agencies, regional agencies, counties, designated planning agencies under N.J.A.C. 7:15, Soil Conservation Districts, regional environmental commissions, Pinelands Commission, mosquito control and extermination commissions, public water supply and wastewater treatment utilities and agencies, lake associations, watershed associations, the watershed management planning area public advisory committee, environmental organizations, businesses, the Department and other appropriate State and Federal agencies and, members of the general public in the drainage area(s) to be addressed by the proposed plan. The solicitation for members of the general public to be part of the regional stormwater management planning committee can be performed through notices in local paper.

(c) The regional stormwater management planning committee shall designate a lead planning agency, which shall be recognized as the primary contact for the committee. The regional stormwater management planning committee, through the lead planning agency, shall:

1. Prepare the regional stormwater management plan;

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

2. Coordinate the regional stormwater management planning process with any applicable watershed management area planning process;

3. Provide opportunities for public participation throughout the regional stormwater management planning process; and

4. Perform other activities appropriate to facilitate the regional stormwater management planning process, including mediation, public information, providing technical assistance, and seeking and providing grants or other financial assistance, as available, to municipalities and/or local or regional agencies pursuant to N.J.S.A. 40:55D-99 or other applicable authority.

(d) A request for recognition as a regional stormwater management planning committee shall be submitted to the Department at the address listed in N.J.A.C. 7:8-1.3 by the lead planning agency, and include the following information:

1. A draft work plan and schedule for completing a regional stormwater management plan;

2. A copy of the mailing list used to solicit participation, including the entities identified in (b) above;

3. A copy of the letter of invitation to participate in the committee;

4. A copy of each response to the letter of invitation; and

5. In cases where no response from a public entity to the letter of invitation is received within 60 days, the group shall send a follow-up request by certified mail, return receipt requested, and submit proof of such follow-up.

(e) The Department shall respond in writing within 45 days of the receipt of a complete request for recognition as a regional stormwater management planning committee. The Department shall either approve the application, request additional information or deny the request for recognition. Denials will include a justification for the decision.

The Department shall base approval or denial on the information submitted in the draft work plan and schedule for plan completion, completion of the requirements to involve and notify impacted parties, and whether there are other competing or overlapping requests for recognition for the same regional stormwater management planning area.

7:8-3.3 Regional stormwater management plan and elements

(a) A regional stormwater management plan shall incorporate, at a minimum, the following elements:

1. Identification of the lead planning agency and a description of the structure and members of the committee;

2. A statement of authority to develop and implement a stormwater management plan from public entities, as appropriate, represented on the regional stormwater management planning committee;

3. A characterization and assessment of the regional stormwater management planning area prepared in accordance with N.J.A.C. 7:8-3.4;

4. A statement of drainage area-specific water quality, groundwater recharge, and water quantity objectives established under N.J.A.C. 7:8-3.5;

5. The drainage area-specific stormwater-related water quality, groundwater recharge and water quantity design and performance standards established under N.J.A.C. 7:8-3.6;

6. The stormwater management measures selected in accordance with N.J.A.C. 7:8-3.7 and a summary of the rationale for the selection of each measure;

7. A description of the strategy for implementing the selected stormwater management measures for the regional stormwater management planning area and for evaluating the effectiveness of the regional stormwater management plan in accordance with N.J.A.C. 7:8-3.8, including a long-term monitoring program; and

8. To the extent elements of the plan do not represent the consensus of the committee, the plan shall identify and provide a discussion of the majority and minority positions.

(b) The regional stormwater management plan may also include:

1. Innovative stormwater measures and strategies such as nonpoint source pollutant trading, mitigation strategies, or special protection measures; and

2. A stream corridor protection plan to address protection of areas adjacent to water-bodies.

7:8-3.4 Characterization and assessment of the regional stormwater management planning area

(a) The regional stormwater management plan shall include a characterization and assessment that addresses the following components, unless the committee determines that a component is not appropriate for the regional stormwater management planning area and provides a rationale for not including the component:

1. Maps showing the following information. Maps developed on a Geographical Information System shall meet the Digital Data standards in N.J.A.C. 7:1D unless a rationale for a different format is provided.

i. The regional stormwater management planning area boundary;

ii. Existing land uses;

iii. Projected land uses assuming full development under existing zoning;

iv. Soil mapping units based on the detailed soil maps in County Soil Surveys published by the U.S. Department of Agriculture or, in areas for which County Soil Surveys are not available, on information obtained from Soil Conservation Districts;

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

v. Topography based on the U.S. Geological Survey Topographic Map, 7.5 minute quadrangle series, or other sources of information depicting topography in similar or greater detail;

vi. Water bodies based on detailed map sheets in County Soil Surveys published by the U.S. Department of Agriculture; the U.S. Geological Survey Topographic Map, 7.5 minute quadrangle series; or other sources of information depicting water bodies in similar or greater detail;

vii. Coastal wetlands based on maps prepared by the Department under the Wetlands Act of 1970, N.J.S.A. 13:9A-1 et seq., and freshwater wetlands based on maps prepared by the Department under the Freshwater Wetlands Protection Act, N.J.S.A. 13:9B-1 et seq.;

viii. Flood hazard areas based on delineations made by the Department under the Flood Hazard Area Control Act, N.J.S.A. 58:16A-50 et seq. For a water body for which the Department has not delineated the flood hazard area, a map of the flood hazard area prepared in accordance with N.J.A.C. 7:13 is acceptable;

ix. Groundwater recharge areas and well head protection areas based on maps prepared by the Department or ordinances of an affected municipality;

x. Environmentally constrained areas and environmentally critical areas;

xi. River areas designated under the New Jersey Wild and Scenic Rivers Act, N.J.S.A. 13:8-45 et seq., or the Federal Wild and Scenic Rivers Act, 16 U.S.C. §§ 1278 et seq.;

xii. For each waterbody in the regional stormwater management planning area, identification of the waterbody or waterbody segment, the drainage area, and the classification of the waterbody pursuant to N.J.A.C. 7:9B-1.15;

xiii. Each waterbody designated as a water quality limited surface water pursuant to N.J.A.C. 7:15-6;

xiv. Man-made stormwater conveyance, storage and discharge systems, including municipal separate storm sewer outfall pipes and the drainage areas as appropriate for these outfall structures; and

xv. Source water areas of potable public surface water supply intakes and public water supply reservoirs available on the Department's webpage at www.nj.gov/dep/swap;

2. A map showing jurisdictional boundaries within the regional stormwater management planning area of municipal, county, and other agencies with responsibility for implementing stormwater management;

3. Identification of the physical characteristics of the regional stormwater management planning area pertinent to stormwater management, such as slopes, swales and impoundment areas as necessary for completing the analysis in N.J.A.C. 7:8-3.4(a)4;

4. A water quality, groundwater recharge and water quantity hydrologic and hydraulic model or analysis of the regional stormwater management planning area which addresses

existing land uses and projected land uses assuming full development under existing zoning and taking into account permanently preserved lands;

5. An identification and evaluation of existing municipal, county, State, Federal, and other stormwater-related groundwater recharge, water quality and water quantity regulations and programs shall be conducted, including, where applicable, programs to develop total maximum daily loads (TMDLs) in accordance with N.J.A.C. 7:15-7; and

6. A summary of information that has been identified as useful for purposes of stormwater management planning but that is not available for technical, financial, or other reasons.

(b) The Department encourages the use of existing information to the extent that it is available to minimize the cost of data acquisition, such as information available on the Department's Geographical Information System website (www.state.nj.us/dep/gis) or as developed through a watershed planning process.

(c) The characterization and assessment shall include information on locations and activities outside the regional stormwater management planning area that drain into the planning area (for example, stormwater originating in an adjacent drainage area that is transferred to the stormwater management planning area).

(d) Using the modeling or other information obtained under (a) through (c) above, the stormwater-related water quality impacts of existing land uses and projected land uses assuming full development under existing zoning shall be identified and ranked in accordance with the following process:

1. Inventory existing and potential stormwater-related pollutant sources and stormwater-related pollutants in the regional stormwater management planning area.

i. Stormwater-related pollutant sources include, for example, urban and suburban development, roads, storm sewers, agriculture, mining, and waterfront development.

ii. Stormwater-related pollutants include, for example, nutrients, pathogens, hydrocarbons, metals, pesticides, sediments, and suspended solids;

2. For surface water bodies and/or segments thereof and aquifers and/or portions thereof in the regional stormwater management planning area, identify and describe the existing or designated uses that are or may be adversely affected by stormwater-related pollutants, and to the extent feasible, identify the source(s) of the pollutant. The use of the report and list prepared by the Department to comply with Federal Clean Water Act, Section 303(d) and 305(b) (33 U.S.C. §§ 1313(d) and 1315(b)) and underlying data, including biological assessments, is encouraged; and

3. Identify and rank the most significant existing and potential stormwater-related pollutants and, for each pollutant, identify and rank the sources.

(e) Using the modeling or other information obtained under (a) through (c) above for stormwater-related water quantity impacts and stormwater-related groundwater recharge impacts of existing and projected land uses assuming full development under existing zoning, the most significant existing and potential stormwater-related water quantity problems, including flooding, erosion, mosquitoes, base-flow reduction, groundwater depletion, and

associated ecosystem impacts, shall be identified and described. The problems shall be ranked based on consideration of threat to public health, safety, and welfare as evidenced by history of or potential for flood damage; risk of loss of or damage to water supplies; and risk of damage to the biological integrity of water bodies.

7:8-3.5 Drainage area-specific water quality, groundwater recharge and water quantity objectives

(a) The regional stormwater management plan shall identify drainage area-specific water quality, groundwater recharge and water quantity objectives that are consistent with the goals of stormwater management planning at N.J.A.C. 7:8-2.3, and address each of the stormwater-related pollutant sources and pollutants ranked under N.J.A.C. 7:8-3.4(d) and the water quantity and groundwater recharge problems ranked under N.J.A.C. 7:8-3.4(e). The objectives shall address the elimination, reduction, or minimization of stormwater-related impacts associated with new and existing land uses. The objectives developed for the regional stormwater management plan may take into consideration environmental, social, and economic factors.

(b) Notwithstanding (a) above, the drainage area-specific objectives for major development shall provide, at a minimum, the protection that would be achieved through the application of N.J.A.C. 7:8-5, Design and Performance Standards for Stormwater Management Measures.

(c) If a TMDL has been established pursuant to N.J.A.C. 7:15 for a waterbody or waterbody segment in the regional stormwater management planning area, drainage area-specific objectives shall incorporate the loading reductions established in the TMDL for stormwater sources of pollution. In addition, if a waterbody or waterbody segment in the regional stormwater management planning area is on the Department's list prepared to comply with Federal Clean Water Act, Section 303(d) (33 U.S.C. § 1313(d)) for one or more designated uses by stormwater runoff, then drainage area objectives shall be included that address the pollutants or pollution for which the waterbody is threatened or impaired.

7:8-3.6 Drainage area-specific design and performance standards

(a) The regional stormwater management plan shall identify drainage area-specific design and performance standards in order to meet the drainage area-specific water quality, groundwater recharge and water quantity objectives identified under N.J.A.C. 7:8-3.5.

(b) Drainage area-specific design and performance standards may include performance standards for control of stormwater quantity, erosion, groundwater recharge and stormwater quality, as well as design standards for particular structural and nonstructural stormwater management strategies.

(c) The design and performance standards for stormwater management measures for major development described in N.J.A.C. 7:8-5 shall be incorporated into the regional storm-

water management plan. Alternative drainage area-specific design and performance standards may be developed provided the alternative standard is at least as protective as would be achieved under N.J.A.C. 7:8-5 when considered on a regional stormwater management planning area basis.

(d) For structural stormwater management measures, drainage area-specific design and performance standards shall conform to the general standards at N.J.A.C. 7:8-5.7.

(e) Drainage area-specific design and performance standards do not have to be uniform throughout a drainage area provided the drainage area, when considered in its entirety, satisfies N.J.A.C. 7:8-5.

7:8-3.7 Selection of stormwater management measures

(a) The regional stormwater management plan shall identify stormwater management measures necessary to achieve the drainage area-specific water quality, groundwater recharge and water quantity objectives developed in accordance with N.J.A.C. 7:8-3.5, and design and performance standards developed in accordance with N.J.A.C. 7:8-3.6.

(b) Stormwater management measures in the following categories shall be considered and selected, as appropriate:

1. Stormwater management measures for new land uses;

2. Stormwater management measures for existing land uses, including, for example, retrofit measures for the modification of existing structural stormwater management measures or other structures affecting stormwater runoff; elimination of illicit or illegal discharges; prevention or minimization of the exposure of pollutants to stormwater; and control of floatables;

3. Stormwater management measures that enhance, protect, and/or preserve land or water areas possessing characteristics or features that provide for flood control, maintenance or improvement of water quality, or conservation of natural resources (for example, land use controls, local and regional open space plans and taxes, buffer zones, redirecting, recharging or minimizing stormwater discharges, pretreatment and/or end-of-pipe treatment); and

4. Public education programs that address stormwater quantity and quality.

(c) A written rationale shall be provided for each selected stormwater management measure, including an analysis of feasibility, benefits and costs, estimated percent pollutant load reduction and anticipated performance longevity;

(d) Each selected stormwater management measure shall include, as appropriate, a program for preventative and corrective maintenance, including a long-term implementation schedule and identification of the entity responsible for implementation and maintenance.

7:8-3.8 Strategy for implementing and evaluating effectiveness of stormwater management measures

(a) The regional stormwater management plan shall include a strategy for implementing the stormwater management measures. The lead planning agency or another entity designated by the committee shall be responsible for coordination and tracking of the implementation of the regional stormwater management plan, including the long-term monitoring program.

(b) The implementation strategy shall:

1. Identify agencies and/or entities necessary to implement the measures and conduct the long-term monitoring program;

2. Identify the respective measures and/or monitoring each agency and/or entity will implement and the enabling mechanisms by which the measures will be implemented, including, for example, new or amended municipal ordinances or interagency agreements;

3. Establish a schedule for the implementation of the measures based on priority, including specific milestones for all mechanisms identified under (b)2 above;

4. Provide an estimate of short term and long term implementation costs to be incurred; and

5. Identify existing and potential private, local, State, and Federal funding sources to implement the regional stormwater management plan.

(c) The implementation strategy shall include a long-term monitoring program that will provide information about land use, water quality, water quantity, groundwater resources and riparian and aquatic habitat condition, as appropriate. Information for the monitoring program may include data obtained through watershed management, local, county, State, interstate, and/or Federal monitoring programs, including volunteer monitoring programs.

(d) The implementation strategy shall include a procedure for evaluating and then updating as necessary, at least every five years, the effectiveness of the implemented measures in achieving the objectives and design and performance standards established in the regional stormwater management plan.

7:8-3.9 Regional stormwater management plan review, adoption, and amendment and/or revision

(a) Upon completion of a regional stormwater management plan, the lead planning agency shall submit the plan to the Department and, if applicable, to the designated water quality management planning agency as an amendment to the areawide water quality management plan(s) in accordance with the Water Quality Management Planning Rules at N.J.A.C. 7:15.

(b) In reviewing a regional stormwater management plan submitted under (a) above, the Department shall determine whether the plan conforms to the requirements of this chapter.

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

The Department will disapprove, return for additional information or proceed with a proposed amendment in accordance with N.J.A.C. 7:15-3.4(g).

(c) Modifications to an adopted regional stormwater management plan shall be processed as an amendment or revision in accordance with N.J.A.C. 7:15-3.4(b)5 or 3.5(b)5, as applicable.

7:8-3.10 Implementation of adopted regional stormwater management plan

(a) Once the regional stormwater management plan has been adopted pursuant to N.J.A.C. 7:8-3.9, implementation responsibilities are as follows:

1. The Department will use the adopted regional stormwater management plan as the basis for reviewing the stormwater management aspects of projects or activities regulated pursuant to Coastal Permit Program rules, N.J.A.C. 7:7; the Freshwater Wetland Protection Act rules, N.J.A.C. 7:7A; the Coastal Zone Management rules, N.J.A.C. 7:7E; the Flood Hazard Area Control Act rules, N.J.A.C. 7:13; the New Jersey Pollutant Discharge Elimination System rules, N.J.A.C. 7:14A; and the Dam Safety Standards, N.J.A.C. 7:20. The requirements of this chapter are considered to be the minimum stormwater standards. Additional requirements may be imposed as necessary under the respective programs.

2. Each municipality in the regional stormwater management planning area shall incorporate the applicable provisions of the regional stormwater management plan into a new or amended municipal stormwater management plan and ordinances.

3. In accordance with the Residential Site Improvement Standards at N.J.A.C. 5:21-7, if a stormwater management plan for the region has been approved by the Department, stormwater management systems must conform with that plan.

4. The Department shall not issue a permit for a project or activity that conflicts with an Areawide Water Quality Management Plan pursuant to N.J.A.C. 7:15-3.1.

SUBCHAPTER 4. MUNICIPAL STORMWATER MANAGEMENT PLANNING

7:8-4.1 Scope

This subchapter describes stormwater management planning and implementation at the municipal level, including plan elements, county review and technical assistance, the schedule for adoption of the plan and ordinances, and variance or exemption from design and performance standards for stormwater management measures.

7:8-4.2 Municipal stormwater management plan and elements

(a) A municipal stormwater management plan shall address stormwater-related water quality, groundwater recharge and water quantity impacts of major development, and may also address stormwater-related water quality, water quantity and groundwater recharge impacts of existing land uses. For purposes of this subchapter, major development is limited to projects that ultimately disturb one or more acres of land.

(b) A municipal stormwater management plan and stormwater control ordinance(s) shall conform with applicable regional stormwater management plan(s).

(c) A municipal stormwater management plan shall, at a minimum:

1. Describe how the municipal stormwater management plan will achieve the goals of stormwater management planning set forth at N.J.A.C. 7:8-2.3;

2. Include maps showing water bodies based on Soil Surveys published by the U.S. Department of Agriculture; the U.S. Geological Survey Topographic Map, 7.5 minute quadrangle series; or other sources of information depicting water bodies in similar or greater detail;

3. Map groundwater recharge areas and well head protection areas based on maps prepared by the Department under N.J.S.A. 58:11A-13 or a municipal ordinance;

4. Describe how the municipal stormwater management plan incorporates design and performance standards in N.J.A.C. 7:8-5 or alternative design and performance standards adopted as a part of a regional stormwater management plan or water quality management plan;

5. Describe how adequate long-term operation as well as preventative and corrective maintenance (including replacement) of the selected stormwater management measures will be ensured;

6. Describe how the plan will ensure compliance with Safety Standards for Stormwater Management Basins at N.J.A.C. 7:8-6;

7. Describe how the municipal stormwater management plan is coordinated with the appropriate Soil Conservation District and any other stormwater management plans, including any adopted regional stormwater management plan, prepared by any stormwater management planning agency related to the river basins or drainage areas to which the plans and/or ordinances apply;

8. Evaluate the extent to which the municipality's entire master plan (including the land use plan element), official map and development regulations (including the zoning ordinance) implement the principles expressed in N.J.A.C. 7:8-5.3(b). This evaluation shall also be included (with updating as appropriate) in the reexamination report adopted under N.J.S.A. 40:55D-89;

9. Include a map of the municipality showing:

i. Projected land uses assuming full development under existing zoning; and

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

ii. The hydrologic unit code 14 (HUC 14) drainage areas as defined by the United States Geological Survey; and an estimate, for each HUC 14 drainage area, of the total acreage in the municipality of impervious surface and associated future nonpoint source pollutant load assuming full build out of the projected land uses.

10. At the option of the municipality, document that it has a combined total of less than one square mile of vacant or agricultural lands rather than provide the information required in (c)8 and 9 above. Agricultural lands may be excluded if the development rights to these lands have been permanently purchased or restricted by covenant, easement or deed. Vacant or agricultural lands in environmentally constrained areas may be excluded if the documentation also includes an overlay map of these areas at the same scale as the map under (c)10i below.

i. Documentation shall include an existing land use map at an appropriate scale to display the land uses of each parcel within the municipality. Such a map shall display the following land uses: residential (which may be divided into single family, two-to-four family, and other multi-family), commercial, industrial, agricultural, parkland, other public uses, semipublic uses, and vacant land;

11. In order to grant a variance or exemption from the design and performance standards in N.J.A.C. 7:8-5, include a mitigation plan that identifies what measures are necessary to offset the deficit created by granting the variance or exemption. The mitigation plan shall ensure that mitigation is completed within the drainage area and for the performance standard for which the variance or exemption was granted;

12. Include a copy of the recommended implementing stormwater control ordinance(s) requiring stormwater management measures; and

13. The municipal stormwater management plan may also include a stream corridor protection plan to address protection of areas adjacent to waterbodies.

7:8-4.3 Schedule for adoption of municipal stormwater management plan and ordinances

(a) A municipality shall adopt a municipal stormwater management plan as an integral part of its master plan and official map in accordance with the schedule in (a)1 or 2 below, whichever is sooner. The requirements in N.J.A.C. 7:8-4.2(c)8 and 9 are not operative until February 2, 2006.

1. By the deadline established in a New Jersey Pollutant Discharge Elimination System permit obtained by the municipality for a municipal separate storm sewer system under N.J.A.C. 7:14A; or

2. By the next reexamination of the master plan under N.J.S.A. 40:55D-89, if a grant for 90 percent of the costs for the preparation of the municipal stormwater management plan has been made available to a municipality by the Department;

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

(b) Within one year after the municipality adopts the municipal stormwater management plan, the municipality shall adopt stormwater control ordinance(s) to implement the adopted plan and shall submit the adopted municipal stormwater management plan and ordinance(s) to the county review agency for approval. The adopted municipal stormwater management plan and ordinance(s) shall not take effect without approval by the county review agency.

(c) The municipality shall amend the municipal stormwater management plan and stormwater control ordinance(s) as necessary and submit the amended plan and amended ordinance(s) to the county review agency for approval.

(d) The municipality shall reexamine the municipal stormwater management plan at each reexamination of the municipality's master plan in accordance with N.J.S.A. 40:55D-89.

(e) Within one year of the adoption of a regional stormwater management plan as an amendment to the Areawide Water Quality Management Plan, or an amendment thereto, each municipality within the regional stormwater management planning area shall amend their respective municipal stormwater management plans and stormwater control ordinance(s) to implement the regional stormwater management plan.

7:8-4.4 County review process

(a) A municipality shall submit a copy of the adopted stormwater management plan and stormwater control ordinance(s) to the county review agency and the Department.

(b) In reviewing the adopted municipal stormwater management plan and ordinance(s), the county review agency shall consider whether the plan and ordinance(s) conform with the requirements of this chapter.

(c) In accordance with N.J.S.A. 40:55D-97, it is the county review agency's responsibility to review and approve, conditionally approve (specifying the necessary amendments to the plan and ordinance(s)) or disapprove the adopted municipal stormwater management plan and ordinance(s) within 60 calendar days of receipt of the plan and ordinance(s). If the county review agency does not approve, conditionally approve, or disapprove the plan or ordinance(s) within 60 calendar days, the plan and ordinance(s) shall be deemed approved. The county review agency shall issue a written decision to the municipality, with a copy to the Department.

(d) A municipal stormwater management plan and ordinance(s) approved under (c) above shall take effect immediately. A municipal stormwater management plan and ordinance(s) conditionally approved under (c) above shall take effect upon adoption by the municipality of the amendments specified by the county review agency.

(e) Within 30 days of the effective date of the municipal stormwater management plan and ordinance(s) under (d) above, the municipality shall place the plan and ordinance(s) on its website and notify the Department, the Soil Conservation District and State Soil Conservation Committee, or:

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

1. Submit a copy of the approved municipal stormwater management plan and ordinance(s) to the Department; and

2. Provide notice of such approval to the Soil Conservation District and the State Soil Conservation Committee and, upon request, submit a copy of the approved plan and ordinance(s).

7:8-4.5 Reservation of rights

The Department reserves the right to review stormwater management plans and ordinances for compliance with this subchapter and make recommendations to correct any deficiencies.

7:8-4.6 Variance or exemption from the design and performance standards for stormwater management measures

A municipality may grant a variance or exemption from the design and performance standards for stormwater management measures set forth in its approved municipal stormwater management plan and stormwater control ordinance(s), provided the municipal plan includes a mitigation plan in accordance with N.J.A.C. 7:8-4.2(c)11 and the municipality submits a written report to the county review agency and the Department describing the variance or exemption and the required mitigation.

SUBCHAPTER 5. DESIGN AND PERFORMANCE STANDARDS FOR STORMWATER MANAGEMENT MEASURES

7:8-5.1 Scope

(a) This subchapter establishes design and performance standards for stormwater management measures for (a) major development intended to minimize the adverse impact of stormwater runoff on water quality and water quantity and loss of groundwater recharge in receiving water bodies.

(b) The standards specified in this subchapter do not apply to major development if alternative design and performance standards that are at least as protective as would be achieved through this subchapter when considered on a regional stormwater management area basis are applicable under a regional stormwater management plan adopted in accordance with this chapter or a water quality management plan adopted in accordance with N.J.A.C. 7:15.

7:8-5.2 Stormwater management measures for major development

(a) Stormwater management measures for major development shall be developed to meet the erosion control, groundwater recharge, stormwater runoff quantity, and stormwater runoff quality standards at N.J.A.C. 7:8-5.4 and 5.5. To the maximum extent practicable, these standards shall be met by incorporating nonstructural stormwater management strategies at N.J.A.C. 7:8-5.3 into the design. If these measures alone are not sufficient to meet these standards, structural stormwater management measures at N.J.A.C. 7:8-5.7 necessary to meet these standards shall be incorporated into the design.

(b) The development shall incorporate a maintenance plan under N.J.A.C. 7:8-5.8 for the stormwater management measures.

(c) Stormwater management measures shall avoid adverse impacts of concentrated flow on habitat for threatened and endangered species as documented in the Department's Landscape Project or Natural Heritage Database established under N.J.S.A. 13:1B-15.147 through 15.150, particularly *Helonias bullata* (swamp pink) and/or *Clemmys muhlenbergi* (bog turtle).

(d) The following linear development projects are exempt from the groundwater recharge, stormwater runoff quantity, and stormwater runoff quality requirements at N.J.A.C. 7:8-5.4 and 5.5:

1. The construction of an underground utility line provided that the disturbed areas are revegetated upon completion;
2. The construction of an aboveground utility line provided that the existing conditions are maintained to the maximum extent practicable; and
3. The construction of a public pedestrian access, such as a sidewalk or trail with a maximum width of 14 feet, provided that the access is made of permeable material.

(e) A waiver from strict compliance from the groundwater recharge, stormwater runoff quantity, and stormwater runoff quality requirements at N.J.A.C. 7:8-5.4 and 5.5 may be obtained for the enlargement of an existing public roadway or railroad, or the construction or enlargement of a public pedestrian access, provided that the following conditions are met:

1. The applicant demonstrates that there is a public need for the project that cannot be accomplished by any other means;
2. The applicant demonstrates through an alternatives analysis, that through the use of nonstructural and structural stormwater management strategies and measures, the option selected complies with the requirements of N.J.A.C. 7:8-5.4 and 5.5 to the maximum extent practicable;
3. The applicant demonstrates that, in order to meet the requirements at N.J.A.C. 7:8-5.4 and 5.5 existing structures currently in use, such as homes and buildings would need to be condemned; and
4. The applicant demonstrates that it does not own or have other rights to areas, including the potential to obtain through condemnation lands not falling under (e)3 above within

the upstream drainage area of the receiving stream, that would provide additional opportunities to mitigate for requirements of N.J.A.C. 7:8-5.4 and 5.5 that were not achievable on-site.

7:8-5.3 Nonstructural stormwater management strategies

(a) To the maximum extent practicable, the standards in N.J.A.C. 7:8-5.4 and 5.5 shall be met by incorporating nonstructural stormwater management strategies at N.J.A.C. 7:8-5.3 into the design. The person submitting an application for review shall identify the nonstructural strategies incorporated into the design of the project. If the applicant contends that it is not feasible for engineering, environmental, or safety reasons to incorporate any nonstructural stormwater management strategies identified in (b) below into the design of a particular project, the applicant shall identify the strategy and provide a basis for the contention.

(b) Nonstructural stormwater management strategies incorporated into site design shall:

1. Protect areas that provide water quality benefits or areas particularly susceptible to erosion and sediment loss;
2. Minimize impervious surfaces and break up or disconnect the flow of runoff over impervious surfaces;
3. Maximize the protection of natural drainage features and vegetation;
4. Minimize the decrease in the "time of concentration" from pre-construction to post-construction. "Time of concentration" is defined as the time it takes for runoff to travel from the hydraulically most distant point of the drainage area to the point of interest within a watershed;
5. Minimize land disturbance including clearing and grading;
6. Minimize soil compaction;
7. Provide low-maintenance landscaping that encourages retention and planting of native vegetation and minimizes the use of lawns, fertilizers and pesticides;
8. Provide vegetated open-channel conveyance systems discharging into and through stable vegetated areas; and
9. Provide other source controls to prevent or minimize the use or exposure of pollutants at the site in order to prevent or minimize the release of those pollutants into stormwater runoff. These source controls include, but are not limited to:
 - i. Site design features that help to prevent accumulation of trash and debris in drainage systems;
 - ii. Site design features that help to prevent discharge of trash and debris from drainage systems;
 - iii. Site design features that help to prevent and/or contain spills or other harmful accumulations of pollutants at industrial or commercial developments; and

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

iv. When establishing vegetation after land disturbance, applying fertilizer in accordance with the requirements established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq., and implementing rules.

(c) Any land area used as a non-structural stormwater management measure to meet the performance standards in N.J.A.C. 7:8-5.4 and 5.5 shall be dedicated to a government agency, subjected to a conservation restriction filed with the appropriate County Clerk's office, or subject to Department approved or equivalent restriction that ensures that measure or an equivalent stormwater management measure approved by the reviewing agency is maintained in perpetuity.

(d) Guidance for nonstructural stormwater management strategies is available in the New Jersey Stormwater Best Management Practices Manual available from the Department through the address listed at N.J.A.C. 7:8-1.3.

7:8-5.4 Erosion control, groundwater recharge and runoff quantity standards

(a) This section contains minimum design and performance standards to control erosion, encourage and control infiltration and groundwater recharge, and control stormwater runoff quantity impacts of major development.

1. The minimum design and performance standards for erosion control are those established under the Soil Erosion and Sediment Control Act, N.J.S.A. 4:24-39 et seq. and implementing rules.

2. The minimum design and performance standards for groundwater recharge are as follows:

i. The design engineer shall, using the assumptions and factors for stormwater runoff and groundwater recharge calculations at N.J.A.C. 7:8-5.6, either:

(1) Demonstrate through hydrologic and hydraulic analysis that the site and its stormwater management measures maintain 100 percent of the average annual pre-construction groundwater recharge volume for the site; or

(2) Demonstrate through hydrologic and hydraulic analysis that the increase of stormwater runoff volume from pre-construction to post-construction for the two-year storm is infiltrated.

ii. This groundwater recharge requirement does not apply to projects within the "urban redevelopment area," or to projects subject to (a)2iii below.

iii. The following types of stormwater shall not be recharged:

(1) Stormwater from areas of high pollutant loading. High pollutant loading areas are areas in industrial and commercial developments where solvents and/or petroleum products are loaded/unloaded, stored, or applied, areas where pesticides are loaded/unloaded or stored; areas where hazardous materials are expected to be present in greater than 'reportable quantities' as defined by the United States

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

Environmental Protection Agency (EPA) at 40 CFR 302.4; areas where recharge would be inconsistent with a remedial action work plan approved pursuant to the Administrative Requirements for the Remediation of Contaminated Sites rules, N.J.A.C. 7:26C, or a Department approved landfill closure plan; and areas with high risks for spills of toxic materials, such as gas stations and vehicle maintenance facilities; and

(2) Industrial stormwater exposed to "source material." "Source material" means any material(s) or machinery, located at an industrial facility, that is directly or indirectly related to process, manufacturing or other industrial activities, which could be a source of pollutants in any industrial stormwater discharge to groundwater. Source materials include, but are not limited to, raw materials; intermediate products; final products; waste materials; by-products; industrial machinery and fuels, and lubricants, solvents, and detergents that are related to process, manufacturing, or other industrial activities that are exposed to stormwater.

iv. The design engineer shall assess the hydraulic impact on the groundwater table and design the site so as to avoid adverse hydraulic impacts. Potential adverse hydraulic impacts include, but are not limited to, exacerbating a naturally or seasonally high water table so as to cause surficial ponding, flooding of basements, or interference with the proper operation of subsurface sewage disposal systems and other subsurface structures in the vicinity or downgradient of the groundwater recharge area.

3. In order to control stormwater runoff quantity impacts, the design engineer shall, using the assumptions and factors for stormwater runoff calculations at N.J.A.C. 7:8-5.6, complete one of the following:

i. Demonstrate through hydrologic and hydraulic analysis that for stormwater leaving the site, post-construction runoff hydrographs for the two, 10 and 100-year storm events do not exceed, at any point in time, the pre-construction runoff hydrographs for the same storm events;

ii. Demonstrate through hydrologic and hydraulic analysis that there is no increase, as compared to the pre-construction condition, in the peak runoff rates of stormwater leaving the site for the two, 10 and 100-year storm events and that the increased volume or change in timing of stormwater runoff will not increase flood damage at or downstream of the site. This analysis shall include the analysis of impacts of existing land uses and projected land uses assuming full development under existing zoning and land use ordinances in the drainage area;

iii. Design stormwater management measures so that the post-construction peak runoff rates for the two, 10 and 100-year storm events are 50, 75 and 80 percent, respectively, of the pre-construction peak runoff rates. The percentages apply only to the post-construction stormwater runoff that is attributable to the portion of the site on which the proposed development or project is to be constructed; or

iv. In tidal flood hazard areas, stormwater runoff quantity analysis in accordance with (a)3i, ii and iii above shall only be applied if the increased volume of stormwater runoff could increase flood damages below the point of discharge.

(b) Any application for a new agricultural development that meets the definition of major development at N.J.A.C. 7:8-1.2 shall be submitted to the Soil Conservation District for review and approval in accordance with the requirements of this section and any applicable Soil Conservation District guidelines for stormwater runoff quantity and erosion control. For purposes of this section, "agricultural development" means land uses normally associated with the production of food, fiber and livestock for sale. Such uses do not include the development of land for the processing or sale of food and the manufacture of agriculturally related products.

7:8-5.5 Stormwater runoff quality standards

(a) Stormwater management measures shall be designed to reduce the post-construction load of total suspended solids (TSS) in stormwater runoff generated from the water quality design storm by 80 percent of the anticipated load from the developed site, expressed as an annual average. Stormwater management measures shall only be required for water quality control if an additional one-quarter acre of impervious surface is being proposed on a development site. The requirement to reduce TSS does not apply to any stormwater runoff in a discharge regulated under a numeric effluent limitation for TSS imposed under the New Jersey Pollutant Discharge Elimination System (NJPDES) rules, N.J.A.C. 7:14A, or in a discharge specifically exempt under a NJPDES permit from this requirement. The water quality design storm is 1.25 inches of rainfall in two hours. Water quality calculations shall take into account the distribution of rain from the water quality design storm, as reflected in Table 1 below. The calculation of the volume of runoff may take into account the implementation of non-structural and structural stormwater management measures.

Table 1: Water Quality Design Storm Distribution

Time (Minutes)	Cumulative Rainfall (Inches)	Time (Minutes)	Cumulative Rainfall (Inches)
0	0.0000	65	0.8917
5	0.0083	70	0.9917
10	0.0166	75	1.0500
15	0.0250	80	1.0840
20	0.0500	85	1.1170
25	0.0750	90	1.1500
30	0.1000	95	1.1750
35	0.1330	100	1.2000
40	0.1660	105	1.2250
45	0.2000	110	1.2334
50	0.2583	115	1.2417
55	0.3583	120	1.2500
60	0.6250		

(b) For purposes of TSS reduction calculations, Table 2 below presents the presumed removal rates for certain BMPs designed in accordance with the New Jersey Stormwater Best Management Practices Manual. The BMP Manual may be obtained from the address identified in N.J.A.C. 7:8-1.3 or found on the Department's website at www.njstormwater.org. The BMP Manual and other sources of technical guidance are

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

listed in N.J.A.C. 7:8-5.9(a). TSS reduction shall be calculated based on the removal rates for the BMPs in Table 2 below. Alternative removal rates and methods of calculating removal rates may be used if the design engineer provides documentation demonstrating the capability of these alternative rates and methods to the review agency. Where the Department is not the review agency, a copy of any approved alternative rate or method of calculating the removal rate shall be provided to the Department at the address at N.J.A.C. 7:8-1.3.

(c) If more than one BMP in series is necessary to achieve the required 80 percent TSS reduction for a site, the applicant shall utilize the following formula to calculate TSS reduction:

$$R = A + B - (AXB)/100$$

Where

R = total TSS percent load removal from application of both BMPs, and

A = the TSS percent removal rate applicable to the first BMP

B = the TSS percent removal rate applicable to the second BMP

Table 2: TSS Removal Rates for BMPs

Best Management Practice	TSS Percent Removal Rate
Bioretention Systems	90
Constructed Stormwater Wetland	90
Extended Detention Basin	40-60
Infiltration Structure	80
Manufactured Treatment Device	See N.J.A.C. 7:8-5.7(d)
Sand Filter	80
Vegetative Filter Strip	60-80
Wet Pond	50-90

(d) If there is more than one onsite drainage area, the 80 percent TSS removal rate shall apply to each drainage area, unless the runoff from the subareas converge on site in which case the removal rate can be demonstrated through a calculation using a weighted average.

(e) Stormwater management measures shall also be designed to reduce, to the maximum extent feasible, the post-construction nutrient load of the anticipated load from the developed site in stormwater runoff generated from the water quality design storm. In achieving reduction of nutrients to the maximum extent feasible, the design of the site shall include nonstructural strategies and structural measures that optimize nutrient removal while still achieving the performance standards in N.J.A.C. 7:8-5.4 and 5.5.

(f) Additional information and examples are contained in the New Jersey Stormwater Best Management Practices Manual, which may be obtained from the address identified in N.J.A.C. 7:8-1.3.

(g) In accordance with the definition of FW1 at N.J.A.C. 7:9B-1.4, stormwater management measures shall be designed to prevent any increase in stormwater runoff to waters classified as FW1.

(h) The Flood Hazard Area Control Act Rules at N.J.A.C. 7:13-4.1(c)1 establish 300-foot riparian zones along Category One waters, as designated in the Surface Water Quality Standards at N.J.A.C. 7:9B, and certain upstream tributaries to Category One waters. A person shall not undertake a major development that is located within or discharges into a 300-foot riparian zone without prior authorization from the Department under N.J.A.C. 7:13.

(i) Pursuant to the Flood Hazard Area Control Act Rules at N.J.A.C. 7:13-11.2(j)4, runoff from the water quality design storm that is discharged within a 300-foot riparian zone shall be treated in accordance with this section to reduce the post-construction load of total suspended solids by 95 percent of the anticipated load from the developed site, expressed as an annual average.

7:8-5.6 Calculation of stormwater runoff and groundwater recharge

(a) Stormwater runoff shall be calculated in accordance with the following:

1. The design engineer shall calculate runoff using one of the following methods:

i. The USDA Natural Resources Conservation Service (NRCS) methodology, including the NRCS Runoff Equation and Dimensionless Unit Hydrograph, as described in Section 4, National Engineering Handbook (NEH-4), dated July 2002, incorporated herein by reference as amended and supplemented. This methodology is additionally described in Technical Release 55--Urban Hydrology for Small Watersheds (TR-55), dated June 1986, incorporated herein by reference as amended and supplemented. Information regarding the methodology is available from the Natural Resources Conservation Service website at <http://www.wcc.nrcs.usda.gov/water/quality/common/neh630/4content.html> or at Natural Resources Conservation Service, 220 Davison Avenue, Somerset, New Jersey 08873; (732) 537-6040; or

ii. The Rational Method for peak flow and the Modified Rational Method for hydrograph computations. The rational and modified rational methods are described in "Appendix A-9 Modified Rational Method" in the Standards for Soil Erosion and Sediment Control in New Jersey, July 1999. This document is available from the State Soil Conservation Committee or any of the Soil Conservation Districts listed at N.J.A.C. 2:90-1.3(a)4. The location, address, and telephone number of each Soil Conservation District is available from the State Soil Conservation Committee, P.O. Box 330, Trenton, NJ 08625, 609-292-5540.

2. For the purpose of calculating runoff coefficients and groundwater recharge, there is a presumption that the pre-construction condition of a site or portion thereof is a wooded land use with good hydrologic condition. The term "runoff coefficient" applies to both the NRCS methodology at N.J.A.C. 7:8-5.6(a)1i and the Rational and Modified Rational Methods at N.J.A.C. 7:8-5.6(a)1i. A runoff coefficient or a groundwater recharge land cover for an existing condition may be used on all or a portion of the site if the design engineer verifies that the hydrologic condition has existed on the site or portion of the site for at least five years without interruption prior to the time of application. If more than one land cover has existed on the site during the five years immediately prior to the time of application, the land cover with the lowest runoff potential shall be used for the computations. In addition, there is the presumption that the site is in good hydrologic condition (if the land use type is pasture, lawn, or park), with good cover (if the land use type is woods), or with good hydrologic condition and conservation treatment (if the land use type is cultivation).

3. In computing pre-construction stormwater runoff, the design engineer shall account for all significant land features and structures, such as ponds, wetlands, depressions, hedgerows, or culverts, that may reduce pre-construction stormwater runoff rates and volumes.

4. In computing stormwater runoff from all design storms, the design engineer shall consider the relative stormwater runoff rates and/or volumes of pervious and impervious surfaces separately to accurately compute the rates and volume of stormwater runoff from the site. To calculate runoff from unconnected impervious cover, urban impervious area modifications as described in the NRCS Technical Release-55, Urban Hydrology for Small Watersheds or other methods may be employed.

5. If the invert of the outlet structure of a stormwater management measure is below the flood hazard design flood elevation as defined at N.J.A.C. 7:13, the design engineer shall take into account the effects of tailwater in the design of structural stormwater management measures.

(b) Groundwater recharge may be calculated in accordance with the following:

1. The New Jersey Geological Survey Report GSR-32 A Method for Evaluating Groundwater-Recharge Areas in New Jersey, incorporated herein by reference as amended and supplemented. Information regarding the methodology is available from the New Jersey Stormwater Best Management Practices Manual; at the New Jersey Geological Survey website at <http://www.state.nj.us/dep/njgs/>; or at New Jersey Geological Survey, 29 Arctic Parkway, PO Box 427, Trenton, NJ 08625-0427; (609) 984-6587.

7:8-5.7 Standards for structural stormwater management measures

(a) Standards for structural stormwater management measures are as follows:

1. Structural stormwater management measures shall be designed to take into account the existing site conditions, including, for example, environmentally critical areas; wetlands; flood-prone areas; slopes; depth to seasonal high water table; soil type, permeability and

texture; drainage area and drainage patterns; and the presence of solution-prone carbonate rocks (limestone).

2. Structural stormwater management measures shall be designed to minimize maintenance, facilitate maintenance and repairs, and ensure proper functioning. Trash racks shall be installed at the intake to the outlet structure as appropriate, and shall have parallel bars with one-inch spacing between the bars to the elevation of the water quality design storm. For elevations higher than the water quality design storm, the parallel bars at the outlet structure shall be spaced no greater than one-third the width of the diameter of the orifice or one-third the width of the weir, with a minimum spacing between bars of one inch and a maximum spacing between bars of six inches. In addition, the design of trash racks must comply with the requirements of N.J.A.C. 7:8-6.2(a).

3. Structural stormwater management measures shall be designed, constructed, and installed to be strong, durable, and corrosion resistant. Measures that are consistent with the relevant portions of the Residential Site Improvement Standards at N.J.A.C. 5:21-7.3, 7.4 and 7.5 shall be deemed to meet this requirement.

4. At the intake to the outlet from the stormwater management basin, the orifice size shall be a minimum of two and one-half inches in diameter.

5. Stormwater management basins shall be designed to meet the minimum safety standards for stormwater management basins at N.J.A.C. 7:8-6.

(b) Stormwater management measure guidelines are available in the New Jersey Stormwater Best Management Practices Manual. Other stormwater management measures may be utilized provided the design engineer demonstrates that the proposed measure and its design will accomplish the required water quantity, groundwater recharge and water quality design and performance standards established by this subchapter.

(c) Manufactured treatment devices may be used to meet the requirements of this subchapter, provided the pollutant removal rates are verified by the New Jersey Corporation for Advanced Technology and certified by the Department.

7:8-5.8 Maintenance requirements

(a) The design engineer shall prepare a maintenance plan for the stormwater management measures incorporated into the design of a major development.

(b) The maintenance plan shall contain specific preventative maintenance tasks and schedules; cost estimates, including estimated cost of sediment, debris, or trash removal; and the name, address, and telephone number of the person or persons responsible for preventative and corrective maintenance (including replacement). Maintenance guidelines for stormwater management measures are available in the New Jersey Stormwater Best Management Practices Manual. If the maintenance plan identifies a person other than the developer (for example, a public agency or homeowners' association) as having the responsibility for maintenance, the plan shall include documentation of such person's agreement to assume this responsibility, or of the developer's obligation to dedicate a

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

stormwater management facility to such person under an applicable ordinance or regulation.

(c) Responsibility for maintenance shall not be assigned or transferred to the owner or tenant of an individual property in a residential development or project, unless such owner or tenant owns or leases the entire residential development or project.

(d) If the person responsible for maintenance identified under (b) above is not a public agency, the maintenance plan and any future revisions based on (h) below shall be recorded upon the deed of record for each property on which the maintenance described in the maintenance plan must be undertaken.

(e) Preventative and corrective maintenance shall be performed to maintain the function of the stormwater management measure, including repairs or replacement to the structure; removal of sediment, debris, or trash; restoration of eroded areas; snow and ice removal; fence repair or replacement; restoration of vegetation; and repair or replacement of non-vegetated linings.

(f) The person responsible for maintenance identified under (b) above shall maintain a detailed log of all preventative and corrective maintenance for the structural stormwater management measures incorporated into the design of the development, including a record of all inspections and copies of all maintenance-related work orders.

(g) The person responsible for maintenance identified under (b) above shall evaluate the effectiveness of the maintenance plan at least once per year and adjust the plan and the deed as needed.

(h) The person responsible for maintenance identified under (b) above shall retain and make available, upon request by any public entity with administrative, health, environmental or safety authority over the site, the maintenance plan and the documentation required by (f) and (g) above.

(i) Nothing in this section shall preclude the municipality in which the major development is located from requiring the posting of a performance or maintenance guarantee in accordance with N.J.S.A. 40:55D-53.

7:8-5.9 Sources for technical guidance

(a) Technical guidance for stormwater management measures can be found in the documents listed at (a)1 and 2 below, which are available from Maps and Publications, Department of Environmental Protection, 428 East State Street, PO Box 420, Trenton, New Jersey, 08625; telephone (609) 777-1038.

1. Guidelines for stormwater management measures are contained in the New Jersey Stormwater Best Management Practices Manual, 2002 as amended. Information is provided on stormwater management measures such as:

- i. Bioretention systems;

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

- ii. Constructed stormwater wetlands;
- iii. Dry wells;
- iv. Extended detention basins;
- v. Infiltration structures;
- vi. Manufactured treatment devices;
- vii. Pervious paving;
- viii. Sand filters;
- ix. Vegetative filter; and
- x. Wet pond.

2. The New Jersey Department of Environmental Protection Stormwater Management Facilities Maintenance Manual, as amended.

(b) Additional technical guidance for stormwater management measures can be obtained from the following:

1. The "Standards for Soil Erosion and Sediment Control in New Jersey" promulgated by the State Soil Conservation Committee and incorporated into N.J.A.C. 2:90. Copies of these standards may be obtained by contacting the State Soil Conservation Committee or any of the Soil Conservation Districts listed in N.J.A.C. 2:90-1.3(a)4. The location, address, and telephone number of each Soil Conservation District may be obtained from the State Soil Conservation Committee, PO Box 330, Trenton, New Jersey 08625, 609-292-5540;

2. The Rutgers Cooperative Extension Service, 732-932-9306; and

3. The Soil Conservation Districts listed in N.J.A.C. 2:90-1.3(a)4. The location, address, and telephone number of each Soil Conservation District may be obtained from the State Soil Conservation Committee, PO Box 330, Trenton, New Jersey 08625, 609-292-5540.

SUBCHAPTER 6. SAFETY STANDARDS FOR STORMWATER MANAGEMENT BASINS

7:8-6.1 Scope

(a) This subchapter sets forth requirements to protect public safety through the proper design and operation of stormwater management basins. This subchapter applies to any new stormwater management basin.

(b) The provisions of this subchapter are not intended to preempt more stringent municipal or county safety requirements for new or existing stormwater management basins. Municipal and county stormwater management plans and ordinances may, pursuant to their authority, require existing stormwater management basins to be retrofitted to meet one or

more of the safety standards in N.J.A.C. 7:8-6.2(a)2, (b) and (c)1 for trash racks, overflow grates, and escape provisions at outlet structures.

7:8-6.2 Requirements for trash racks, overflow grates and escape provisions

(a) A trash rack is a device designed to catch trash and debris and prevent the clogging of outlet structures. Trash racks shall be installed at the intake to the outlet from the stormwater management basin to ensure proper functioning of the basin outlets in accordance with the following:

1. The trash rack shall have parallel bars, with no greater than six-inch spacing between the bars;
2. The trash rack shall be designed so as not to adversely affect the hydraulic performance of the outlet pipe or structure;
3. The average velocity of flow through a clean trash rack is not to exceed 2.5 feet per second under the full range of stage and discharge. Velocity is to be computed on the basis of the net area of opening through the rack; and
4. The trash rack shall be constructed of rigid, durable, and corrosion resistant material and designed to withstand a perpendicular live loading of 300 lbs./ft sq.

(b) An overflow grate is designed to prevent obstruction of the overflow structure. If an outlet structure has an overflow grate, the grate shall comply with the following requirements:

1. The overflow grate shall be secured to the outlet structure but removable for emergencies and maintenance;
2. The overflow grate spacing shall be no greater than two inches across the smallest dimension; and
3. The overflow grate shall be constructed of rigid, durable, and corrosion resistant material and designed to withstand a perpendicular live loading of 300 lbs./ft sq.

(c) Stormwater management basins shall include escape provisions as follows:

1. If a stormwater management basin has an outlet structure, escape provisions shall be incorporated in or on the structure. Escape provisions include the installation of permanent ladders, steps, rungs, or other features that provide easily accessible means of egress from stormwater management basins. With the prior approval of the reviewing agency pursuant to N.J.A.C. 7:8-6.3, a free-standing outlet structure may be exempted from this requirement;
2. Safety ledges shall be constructed on the slopes of all new stormwater management basins having a permanent pool of water deeper than two and one-half feet. Safety ledges shall be comprised of two steps. Each step shall be four to six feet in width. One step shall be located approximately two and one-half feet below the permanent water surface, and the second step shall be located one to one and one-half feet above the permanent water

THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

surface. See N.J.A.C. 7:8-6 Appendix A for an illustration of safety ledges in a stormwater management basin; and


3. In new stormwater management basins, the maximum interior slope for an earthen dam, embankment, or berm shall not be steeper than three horizontal to one vertical.

7:8-6.3 Variance or exemption from safety standards

A variance or exemption from the safety standards for stormwater management basins may be granted only upon a written finding by the appropriate reviewing agency (municipality, county or Department) that the variance or exemption will not constitute a threat to public safety.

APPENDIX A

Appendix A: Illustration of safety ledges in a new detention basin. Depicted is an elevational view.



THIS IS A COURTESY COPY OF THIS RULE. ALL OF THE DEPARTMENT'S RULES ARE COMPILED IN TITLE 7 OF THE NEW JERSEY ADMINISTRATIVE CODE.

surface. See N.J.A.C. 7:8-6 Appendix A for an illustration of safety ledges in a stormwater management basin; and

3. In new stormwater management basins, the maximum interior slope for an earthen dam, embankment, or berm shall not be steeper than three horizontal to one vertical.

7:8-6.3 Variance or exemption from safety standards

A variance or exemption from the safety standards for stormwater management basins may be granted only upon a written finding by the appropriate reviewing agency (municipality, county or Department) that the variance or exemption will not constitute a threat to public safety.

APPENDIX A

Appendix A: Illustration of safety ledges in a new detention basin. Depicted is an elevational view.

